



Nedo® Product Information

Laser Receiver ACCEPTOR Line with mm display for Nedo red line lasers with pulse mode



Features:

- Suitable for red line lasers with a wavelength of 610-780 nm
- Extremely robust laser receiver
- Large detector field: 50 mm
- Large LC display on front and back
- Adjustable volume
- Strong magnets for fixing to steel girders
- Optionally supplied with quick clamp or Heavy-Duty rod clamp made of diecast aluminium
- mm display
- Automatic switch-off

Technical data:

| | |
|---------------------------|--|
| Accuracy | switchable ± 4.0 mm / ± 1.0 mm |
| Working range \emptyset | 100 m |
| Length of detector field | 50 mm |
| Reception angle | $\pm 65^\circ$ |
| Protection class | IP 67 |
| Operating temperature | - 20°C to + 50°C |
| Power supply | 2 x 1.5 V type mignon (AA) |
| Operation duration | approx. 70 h |



With quick clamp
Ref.-No. 430 336



With Heavy-Duty rod clamp
Ref.-No. 430 337

Technical data subject to change



Precise surveying and measuring

Nedo GmbH & Co. KG
Hochgerichtstrasse 39-43
D-72280 Dornstetten

Phone +49 (0) 7443 24 01-0
Fax +49 (0) 7443 24 01-45

info@nedo.com www.nedo.com