





The clearly arranged key pad allows for easy handling and the reliable, magnetically damped pendulum ensures precise results at all times.

The device will automatically self-level at inclines of up to 4°.





Scope of delivery X-Liner 2: X-Liner 2, universal adapter, ball joint adapter, fixing straps, batteries, target board and carrying case Ref.-No. 460 870



Optional accessory: Laser receiver **ACCEPTOR Line** with mm display.

## **Nedo X-Liner 2**

Self-levelling cross line laser with one vertical and one horizontal line. The highly visible laser cross on the wall allows rapid and precise levelling and alignment. Thanks to the pulse function, the X-Liner 2 can be used with the ACCEPTOR Line laser receiver even in adverse light conditions.

## Features:

- Self-levelling cross line laser for levelling and alignment
- Highly visible horizontal and vertical laser line, can be activated separately
- Pulse function for use with the ACCEPTOR Line laser receiver
- Reliable magnetic damping
- Tilt function
- Universal adapter with strong magnet and 1/4" and 5/8" mounting thread

## **Nedo X-Liner 2**

RefNo.	460 870
Accuracy	± 0.3 mm/m
Self-levelling range	± 4°
Working range Ø	approx. 50 m without laser receiver
	approx. 100 m with laser receiver
Laser	Laser class 2, 635 nm
Protection class	IP 54
Power supply	3 x 1.5 V type mignon / AA
Operation duration	approx. 20 h
Connecting thread	1/4"

